


Medline EXM 80

SPECIFICATIONS



Four international AC plugs included.
AC cable can be delivered as option

INPUT

Nominal input range	100-240VAC.
Voltage range	90-264VAC. 85-99V with 70% output power.
Frequency	50/60Hz.
Input current	1.7A.
Inrush current	Max 50A peak, cold start.
Input connector	C8 cable connector or exchangeable input connectors for Europe, US, UK and Australia.
Leakage current	<100µA.
Isolation class	Class II. Double isolation, type B applied part.
Zero load power consumption	Approx 0,5 Watts at 110 VAC input.

OUTPUT

Power	Up to 80W continuous, see table.
Voltage	See table.
Tolerance	5%.
Ripple and noise	Typ. 1% p-p max (20MHz BW). 5% at ≤100VAC input.
Efficiency	87-90% @ 230VAC full load.
Hold up time	35ms at 230VAC.
Start up time	<2s max.
Line regulation	1% max full load. 5% at ≤100VAC input.
Load regulation	2% max @ 230VAC, 10-90% load change at adapter output terminal. Output cable excluded.
Overcurrent protection	Approx 125%, auto recovery.
Current limiting charact.	Constant current.
Transient response	4ms max, 1ms typical.
Temperature coefficient	Typ 0.04%/°C of Vout.
Output cable	2m, flexible. 1 wire cable, diameter 4mm. Internal wires AWG16 white colour.
Output connector	Barrel plug. 2.5/5.5/9.2mm, centre plus, white colour.
Recommended connector	Cliff type FC 68149, 5.5/2.5mm or FC681446 or equivalents.

ENVIRONMENTAL

Operating temperature	0°C to +40°C.
Storage temperature	-40°C to +75°C.
Humidity	5% to 95% non-condensing.

GENERAL


Switching frequency	40-80kHz.
Dimensions	118 x 45 x 70mm excl ac plugs.
Weight	Max 300g including one ac plug.
Protection class	Designed to meet IP50.
Case	94V0. Polycarbonate. White colour.
MTBF	>300,000 h at 25°C ambient temperature. 50 years power on.
Lifetime prediction	Min 80,000 h at 22°C, 230VAC and 50% load.
Indicator	"On" indicates with green LED.
Cleaning	Use dry towel. Do not soak in water.

STANDARDS

Safety standards	IEC60601-1 including deviations for Europe, US & Canada by Intertek Semko.
Safety markings	S, ETL & CE.
EMC standards	IEC60601-1-2, IEC61204-3.
Harmonic current emissions	IEC61000-3-2.
Voltage fluctuations and flicker	IEC61000-3-3.
ESD susceptibility	IEC61000-4-2, ±6kV contact discharge, ±8kV air discharge.
Radiated susceptibility EFT/Burst	IEC61000-4-3, 3V/m. IEC61000-4-4, ±2kV on AC port, ±1kV on signal ports.
Surge	IEC61000-4-5, ±2kV common mode, ±1kV differential mode.
Conducted susceptibility	IEC61000-4-6, 3V/m
Power frequency magnetic field	IEC61000-4-8, 3A/m.
Dips and interruptions	IEC61000-4-11, 30% 500ms, 60% 100ms, 95% 5sec. Performance criteria A A* B.

* at 100-160 VAC nominal input voltage performance criteria B

AC PLUGS MEDLINE EXM 80



Main standard in all European countries.

Main standard in UK

Main standard in US

Main standard in Australia, New Zealand

MODEL NUMBER	OUTPUT VOLTAGE	CONTINUOUS OUTPUT CURRENT	CONTINUOUS OUTPUT POWER	PEAK OUTPUT CURRENT*)	PEAK OUTPUT POWER*)
EXM 80 5118	12V	5A	60W	5.5A	70W
EXM 80 5119	15V	4A	60W	4.7A	70W
EXM 80 5120	18V	3.6A	65W	4.2A	75W
EXM 80 5121	24V	2.9A	70W	3.3A	80W
EXM 80 5122	48V	1.5A	70W	1.7A	80W

*) Max duration 30 sec. per every 10 minutes.