

TR60M Series

30-60 WATTS - AC/DC SINGLE OUTPUT

FEATURES

- Wide input voltage 90VAC to 264VAC, 50/60Hz
- Continuous short circuit protection
- Over voltage protection
- Output voltage available from 5VDC to 24VDC
- High efficiency 85% typical
- Meets EN55022 Class "B"
- MEPS compliane (Efficiency Mark V pending)



MEDICAL

SPECIFICATIONS

INPUT	
Voltage range	90 to 264VAC
Frequency	47Hz to 63Hz
Inrush current	50A max @ 264VAC.
Isolation	Input to output 5,656VDC.
Leakage current	0.1mA max.
OUTPUT	
Output voltage	Factory preset, see table (not adjustable)
Voltage set-point	+/-2% to +/-4% (60% load)
Ripple and noise	1% p-p max
Short circuit protection	Continuous (Auto recovery)
Over voltage protection	Yes. (option)
Hold-up time	8ms typ @ 115Vac
Load regulation	+/-2 to +/-6% (20% to 100% load)
Line regulation	+/-1% max at full load
ENVIRONMENTAL	
Operating temperature	0°C to +60°C
Storage temperature	-20°C to +85°C
Derating	Derate from 100% at +40°C linearly to 70% at +60°C
Cooling	Natural convection

STANDARDS AND APPROVALS	
Safety standards	EN60601-1 (TBC)
C-Tick	AS/NZS CISPR11 Group 1, Class A (TBC)
EMI standards	CISPR/FCC Class B (TBC)
RCM	Complies AS/NZS 4417 parts, 1, 2, 3 N 911
MECHANICAL	
Dimensions	132x58x30.5mm
Weight	288g
AC Inlet	IEC320/C8.
Output connector	Right angle, hollow coaxial plug, 2.5mm inside diameter; 5.5mm outside diameter; 9.5mm length Center positive polarity.
DC cord length	720mm with ferrite core 18AWG/UL1185.

SELECTION TABLE

MODEL NUMBER	RATED V _{NOM}	OUTPUT CURRENT	MAX POWER
TR60M05-21E11	5Vdc	6.0A	30W
TR60M12-21E11	12Vdc	5.0A	60W
TR60M15-21E11	15Vdc	4.0A	60W
TR60M18-21E11	18Vdc	3.3A	60W
TR60M24-21E11	24Vdc	2.5A	60W

TECHNICAL ILLUSTRATION

