

Site Controller

The site controller, CU-31A F, is the key component to do remote monitoring and management; it can communicate with Delta RMMS software to upload all measurement data and alarm event.

Delta is known for quality and product reliability, and this solution has been added cost effectiveness.



INPUT

EGCEEC-01-TC

Voltage (default)	-54V _{DC}
Voltage (adjustable range)	-18 to -60V _{DC}
Current	2.0A _{DC} (Max.)

MECHANICAL

Dimensions (W x H x D)	425.0 x 44.0 x 304.0mm (16.7 x 1.7 x 12.0in)
Weight	1.8kg (4.0lb)

STANDARDS

Cooling	Natural air flow
Operating Temperature	-40 to +70 °C (-40 to +158 °F)
Relative Humidity	95%, non-condensing

FUNCTIONS**

Analog Input	AI x4
Temperature Detection	Ambient x2
Digital Input	DI x 8
Dry Contact	Free dry contact (DO) x6
DC Current Detection	DC current measurement x5 (via hall sensor)
RS485 Modbus Master	RS485 Modbus RTU x1
RS485 Modbus Slave	Modbus slave RTU for remote monitoring
CANBUS	IMBUS x1 to connect extension modules
Firmware Upgrade	Remote firmware upgrade
Data Log	100,000 data log
Ethernet Port	WAN x1; LAN x5

USER INTERFACE

Communication Protocol	SNMP v1/v2c/v3
Languages	English, Traditional Chinese (default), Japanese (option)

EXTENSIONS (OPTIONAL) **

Delta Standard Module Control/Monitoring	Rectifier, PV charger, LVD control board/AC meter/DC meter
Genset Control/Monitoring	Integrate genset ON/OFF control/monitoring functionality over RS485 Modbus RTU
Configurable DO/DI/AI PLC	PLC functionality for customization and supervision and control of auxiliary devices

ORDERING INFORMATION

Site Controller	CU-31A F-S
Accessories	Signal connectors, cable fixing kits

* All specifications are subject to change without prior notice.

** The optional function is available but need to discussion for different application; please contact Delta solution team for the detail.



Delta Group



Telecom Power Systems

Delta Electronics Inc.

16 Tungyuan Road, Chungli Industrial Zone,
Taoyuan City 32063, Taiwan.

T +886 3 452 6107 / F +886 3 452 7314

www.deltawww.com

Authorised, valued-added distributor

Australia & New Zealand



Powerbox Australia Pty Ltd

Sydney Head Office
4 Beaumont Road,
Mt Kuring-Gai, NSW 2080
Australia



1800 251 380



sales@powerbox.com.au



powerbox.com.au

Powerbox Pacific Ltd

New Zealand Sales Office
1a Henry Rose Place,
Albany, Auckland
New Zealand 0632



09 4158 320



sales@powerbox.co.nz



powerbox.co.nz